

MAN Lion's Intercity 2016 +

Power ignition	Power contin	GND Black	Aux 4	Aux 3	Aux 2	Aux 1	J1708+2	J1708-2	J1708+1	J1708-1	K/L-Line2	K-Line2	K/L-Line1	CAN4-H	CAN4-L	CAN3-H	CAN3-L	CAN2-H	CAN2-L	CAN1-H	CAN1-L	Vehicle spec.	DATAcliQ 6	DATAcliQ 5	DATAcliQ 4	DATAcliQ 3	DATAcliQ 2	DATAcliQ 1	CANcliQ	OBD
Location Find the Fusebox tray located inside a luggage compartment, folded up against the roof. © Squarell 2018														CANbus Untwist the 173/White and 174/White wires Place the 173/White wire in the CAN high slot. Place the 174/White wire in the CAN low slot. Close the CANcliQ. © Squarell 2018																
Power + Ground : Connections in OBD connector. Ground (KL31) : OBD connector pin 4 and pin 5. Continuous Power (KL30) : Pin 16 OBD connector. © Squarell 2018														Power + Ground : Connections in OBD connector. Ground (KL31) : OBD connector pin 4 and pin 5. Continuous Power (KL30) : Pin 16 OBD connector. © Squarell 2018																

Warning! CANcliQ or DatacliQ closes only once. Please repower the Squarell Device after the installation is completed. Please connect Squarell devices to a 10V to 30V power supply. Please use certified crimping tools to connect the wires.